LIMELIGHT® COLLECTION



FreshWater® Salt System Ready



Dual Action Filtration SilentFlo Circulation



FiberCor® High-Density Insulation



Color LCD Display

PULSE®



PeopleSeatingJetsVoltage7 SeatsOpen49 Jets230 V

Size

7'5" x 7'5" x 38" | 226 cm x 226 cm x 97 cm

Water Care

FreshWater® Salt System Ready



LIMELIGHT® COLLECTION

PULSE°





SHELL COLORS*











Alpine Gray

Platinum Desert

Sun

CABINET COLORS*







Coastal Gray

Sable

Espresso

COVER COLORS







Slate

Caramel Chestnut

LEGENDARY MASSAGE

49 Personalized-Control Jets

- · 1XL Dual Rotary jet
- 1 XL Single Rotary jet
- · 2 XL Directional jets
- 4 Standard Single Rotary jets
- 2 Standard Directional jets
- · 4 Rotary Precision jets
- 35 Directional Precision® jets

EASY WATER CARE

Water Care System FreshWater® Salt System Ready Filtration System Dual action, 100 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump 1 Wavemaster® 9200; Two-speed, 2.5 HP Continuous Duty,

5.2 HP Breakdown Torque

Wavemaster® 9000; One-speed, 2.5 HP Continuous Duty, Jet Pump 2

5.2 HP Breakdown Torque

SilentFlo 5000® for quiet, continuous filtration **Circulation Pump**

Titanium No-Fault® 4,000 W / 230 V Heater

Insulation FiberCor® Insulation; Certified to California

> Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

3.5" to 2.5" tapered, 2 lb. density foam core Cover

SIZE

Dimensions 7'5" x 7'5" x 38" / 226 cm x 226 cm x 97 cm

CAPACITY

Seating Capacity 7 seats

445 gallons / 1,685 liters **Water Capacity**

Weight 1,015 lbs. / 460 kg dry; 5,950 lbs. / 2,700 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology Hot Spring Spas App, Powered by the Connected Spa Kit

Water Feature Vidro® backlit ribbon waterfall

Cover Lifters CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Steps

Lighting System

Limelight Collection Step (Coastal Gray, Espresso, and Sable), Polymer Step (Ash)

Entertainment Bluetooth® Wireless Sound System (Optional) **Control System**

IQ 2020® with LCD control panel

230 V / 50 amp, 60 Hz (Includes G.F.C.I. protected sub-panel)

Raio® multi-color interior points of light

Exterior multi-color lighting with timer

CoolZone™ (Optional) **Cooling System**